

MS495-100



Products Low Voltage Products and Systems Circuit Breakers Manual Motor Starters

Products Low Voltage Products and Systems Control Products Manual Motor Starters Manual Motor Starters

General Information

Extended Product Type:	MS495-100
Product ID:	1SAM550000R1010
EAN:	4013614265488
Catalog Description:	MS495-100 Manual Motor Starter
Long Description:	The MS495-100 manual motor starter is a 70 mm width devices with a rated operational current of $I_e = 100.0$ A. This device is used to manually switch on and off motors and to protect them reliably and without the need for a fuse from short-circuits, overload and phase failures. The manual motor starter offers a rated service short-circuit breaking capacity $I_{cs} = 25$ kA at 400 VAC and the trip class 10. Further features are the build-in disconnect function, temperature compensation, trip-free mechanism and a rotary handle with a clear switch position indication. The manual motor starter is suitable for three- and single-phase applications. The handle is lockable to protect against unauthorized changes. Auxiliary contacts, signaling contacts, undervoltage releases and shunt trips are available as accessory.

Additional Information

ATEX Certificate:	1SAA937000-3901
Actuator Type:	Rotary Handle
Ambient Air Temperature:	Operation -20 ... +70 °C Operation Compensated -20 ... +60 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation:	Yes
Ampere Rating UL/CSA:	99 A
BV Certificate:	1SAA937000-0202
CCC Certificate:	1SAA937001-3803
Connecting Capacity Main Circuit UL/CSA:	Flexible 1x 10-2/0 AWG Flexible 1/2x 10-1/0 AWG Stranded 1x 10-2/0 AWG Stranded 1/2x 10-1/0 AWG
Connecting Capacity Main Circuit:	Flexible with Ferrule 1x 2.5 ... 50 mm ² Flexible with Ferrule 2x 2.5 ... 35 mm ² Solid 1/2x 2.5 ... 16 mm ² Stranded 1x 10 ... 70 mm ² Stranded 2x 10 ... 50 mm ²
Contact Position Indication:	ON / OFF / TRIP
Conventional Free-air Thermal Current (I_{th}):	Main Circuit 100 A
Country of Origin:	Germany (DE)
Customs Tariff Number:	85362090
DNV Certificate:	1SAA937000-0302
Data Sheet, Technical Information:	1SBC100173C0201
Data Sheet, Technical Information (Part 2):	1SAM500501F0010
Data Sheet, Technical Information (Part 3):	9AKK105713A1102
Declaration of Conformity - CE:	1SAD938504-0050
Degree of Protection:	Housing IP20 Main Circuit Terminals IP00
E-number:	3112270
EAC Certificate:	1SAA937001-2703
EAN:	4013614265488

EPLAN Catalog Tree:	Electrical engineering / Protection devices / Motor overload switch
EPLAN Function Definition:	Motor overload switch / Motor overload switch, 6 connection points / Motor overload switch three-pole 1_2_3_4_5_6
ETIM 4:	EC000074 - Motor protective circuit-breaker
ETIM 5:	EC000074 - Motor protective circuit-breaker
ETIM 6:	EC000074 - Motor protection circuit-breaker
Electrical Durability:	25000 cycle
Environmental Information:	1SAA918004-2401
GL Certificate:	1SAA937000-0404
GOST Certificate:	1SAA963001-2702
General Use Rating UL/CSA:	(600 V AC) 99 A
Horsepower Rating UL/CSA:	(200 V AC) Three Phase 30 Hp (208 V AC) Three Phase 30 Hp (220 ... 240 V AC) Three Phase 40 Hp (440 ... 480 V AC) Three Phase 75 Hp (550 ... 600 V AC) Three Phase 100 Hp
IT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SAM507001R1001
Instructions and Manuals (Part 2):	2CDC131017M5701
Invoice Description:	MS495-100 Manual Motor Starter
LR Certificate:	1SAA937000-0504
Maximum Operating Altitude Permissible:	2000 m
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Mechanical Durability:	50000 cycle
Minimum Order Quantity:	1 piece
Mounting Position:	Position 1 to 6
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Number of Poles:	3
Number of Protected Poles:	3
Object Classification Code:	F
Package Level 1 EAN:	4013614265488
Package Level 1 Gross Weight:	2.276 kg
Package Level 1 Height:	171 mm
Package Level 1 Length:	190 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	76.5 mm
Phase Loss Sensitive:	Yes
Pollution Degree:	3
Power Loss:	at Rated Operating Conditions per Pole 3.5 ... 5.4 W
Product Main Type:	MS495
Product Name:	Manual Motor Starter
Product Net Depth:	174 mm
Product Net Height:	165 mm
Product Net Weight:	2.295 kg
Product Net Width:	70 mm
RMRS Certificate:	1SAA918000-0704
Rated Current (I_n):	100 A
Rated Frequency (f):	Main Circuit 50 Hz Main Circuit 60 Hz

Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 6 kV
Rated Instantaneous Short-Circuit Current Setting (I_i):	1235 A
Rated Insulation Voltage (U_i):	690 V
Rated Operational Current (I_e):	100 A
Rated Operational Current AC-3 (I_e):	100 A
Rated Operational Power AC-3 (P_e):	(400 V) Three Phase 55 kW
Rated Operational Voltage:	Main Circuit 690 V AC Main Circuit 450 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(230 V AC) 100 kA (400 V AC) 25 kA (440 V AC) 20 kA (500 V AC) 4 kA (690 V AC) 3 kA
Rated Service Short-Circuit Breaking Capacity, in % of I_{cu} (I_{cs}):	50 %
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(230 V AC) 100 kA (400 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 8 kA (690 V AC) 5 kA
Rated Uninterrupted Current (I_u):	100 A
Recommended Screw Driver:	Hexagon 4
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 25g
RoHS Date:	0016
RoHS Information:	1SAA918002-4401
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selectivity Category:	A
Selling Unit of Measure:	piece
Setting Range:	80 ... 100 A
Short Description:	MS495-100 Manual Motor Starter
Short-Circuit Protective Devices:	gG Type Fuses 125 A, 690 V AC gG Type Fuses 160 A, 400 V AC
Standards:	IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1 UL 508 CSA 22.2 No. 14
Suitable for Isolation:	Yes
Tightening Torque:	Main Circuit 4 ... 6 N·m
Tightening Torque UL/CSA:	Main Circuit 35 ... 53 in·lb
Trip Class:	10
UL Certificate:	UL_E167205 UL_E195536
UNSPSC:	39121521
Utilization:	Motor Protection
Wire Stripping Length:	Main Circuit 17 mm
cUL Certificate:	cUL_E195536
eClass:	7.0 27370401

