

## General Information

<b>Extended Product Type:</b>	CT-AHE
<b>Product ID:</b>	1SVR550118R1100
<b>EAN:</b>	4013614346309
<b>Catalog Description:</b>	CT-AHE Time relay, OFF-delay 1c/o, 0.1-10s, 24VAC/DC
<b>Long Description:</b>	The CT-AHE is a single-function electronic time relay from the CT-E timer range. It provides an OFF-delay (delay on break) function with a time range from 0.1 s to 10 s. This time relay operates with a rated control supply voltage of 24 V AC / DC and has a 1 c/o (SPDT) output rated at 250 V / 4 A. A control input works with voltage-related (non-floating) triggering

## Additional Information

<b>Analog Inputs:</b>	0
<b>CB Certificate:</b>	CB_DK-8575
<b>CCC Certificate:</b>	CCC_2010010303393101
<b>Country of Origin:</b>	Bulgaria (BG)
<b>Customs Tariff Number:</b>	85364900
<b>Data Sheet, Technical Information:</b>	2CDC111136D0201
<b>Declaration of Conformity - CE:</b>	1SVD981002-0000
<b>EAC Certificate:</b>	EAC_RU_C-DE.ME77.B.02016
<b>EAN:</b>	4013614346309
<b>EPLAN Catalog Tree:</b>	Electrical engineering / Relays, contactors / General
<b>EPLAN Function Definition:</b>	Coil / Coil with special drive, 3 connection points / Coil, with drop-out delay, 3 connection points A1_A2_Y1 Change-over contact / Change-over contact, 3 connection points / Change-over contact, off-delay 16_15_18
<b>ETIM 4:</b>	EC001439 - Timer relay
<b>ETIM 5:</b>	EC001439 - Timer relay
<b>ETIM 6:</b>	EC001439 - Timer relay
<b>Environmental Information:</b>	1SAA981011-2402
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SVC550000M9000
<b>Invoice Description:</b>	CT-AHE Time relay, OFF-delay 1c/o, 0.1-10s, 24VAC/DC
<b>Minimum Order Quantity:</b>	1 piece
<b>Mounting Position:</b>	Any
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Number of Digital Inputs:</b>	1
<b>Object Classification Code:</b>	K
<b>Output:</b>	1 c/o (SPDT) contact
<b>Package Level 1 EAN:</b>	4013614346309
<b>Package Level 1 Gross Weight:</b>	0.077 kg
<b>Package Level 1 Height:</b>	83.1 mm
<b>Package Level 1 Length:</b>	24.6 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	84.2 mm
<b>Power Loss:</b>	Approximately 2 W

<b>Product Main Type:</b>	CT-AHE
<b>Product Name:</b>	Time Relay
<b>Product Net Depth:</b>	78.5 mm
<b>Product Net Height:</b>	78 mm
<b>Product Net Weight:</b>	0.064 kg
<b>Product Net Width:</b>	22.5 mm
<b>RMRS Certificate:</b>	RMRS_1740021250
<b>Rated Control Supply Voltage (U<sub>s</sub>):</b>	24 V AC/DC
<b>Regulatory Compliance Mark (RCM):</b>	Yes
<b>RoHS Date:</b>	1146
<b>RoHS Information:</b>	1SVD981001-4400
<b>RoHS Status:</b>	Following EU Directive 2011/65/EC
<b>Selling Unit of Measure:</b>	piece
<b>Short Description:</b>	CT-AHE Time relay, OFF-delay
<b>Standards:</b>	IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14
<b>Terminal Type:</b>	Screw Terminals
<b>Time Range:</b>	0.1-10 s
<b>Timer Relay Type:</b>	OFF-Delay
<b>UL Certificate:</b>	UL508_E140448
<b>UNSPSC:</b>	39121500
<b>cUL Certificate:</b>	cUL508_E140448
<b>eClass:</b>	7.0 27371790
<b>DNV GL Certificate:</b>	DNV_GL_TAA00000F2

